

CCH550T

作業半径 [m]	ブーム長 [m]			
	11.4	19.1	26.8	34.5
3.0	55.0	30.0		
3.4	51.0	30.0		
3.5	50.0	30.0	22.0	
4.0	46.4	30.0	22.0	
4.5	42.0	30.0	22.0	
4.8				12.0
5.0	36.4	30.0	22.0	12.0
5.5	30.9	30.0		12.0
5.9			22.0	
6.0	26.7	26.6	21.7	12.0
6.5	23.4	23.4	20.4	12.0
7.0	20.6	20.7	19.0	12.0
8.0	15.8	16.6	16.2	
8.7				12.0
9.0	11.4	13.8	13.8	11.7
9.3	10.3			
10.0		11.6	11.6	10.5
12.0		8.5	8.5	8.5
14.0		6.4	6.4	6.9
16.0		4.9	5.0	5.6
17.0		4.1		
18.0			3.7	4.6
20.0			2.7	3.6
22.0			1.9	2.7
24.0			1.2	2.0
24.7			1.0	
26.0				1.5
28.0				1.0
29.0				0.6

TK550G

作業半径 [m]	ブーム長さ [m]			
	10.0	16.7	23.4	30.1
3.0	55.0	28.0	22.0	14.0
3.5	50.0	28.0	22.0	14.0
4.0	42.5	28.0	22.0	14.0
4.5	36.5	28.0	22.0	14.0
5.0	31.7	28.0	22.0	14.0
5.5	26.9	26.7	22.0	14.0
6.0	23.4	23.1	22.0	14.0
6.5	20.6	20.3	20.2	14.0
7.0	18.3	18.0	17.9	13.5
7.5	12.5	16.2	16.0	13.0
7.7	11.9	15.5	15.4	12.8
8.0		14.6	14.5	12.5
8.5		13.3	13.2	12.0
9.0		12.3	12.0	11.5
9.5		11.3	11.0	11.0
10.0		10.4	10.2	10.7
11.0		9.0	8.7	9.2
12.0		7.8	7.6	8.1
13.0		6.8	6.6	7.1
14.0		6.0	5.8	6.3
14.4		5.6	5.5	6.0
15.0			5.1	5.6
16.0			4.6	5.0
17.0			4.1	4.5
18.0			3.7	4.1
19.0			3.3	3.7
20.0			2.9	3.3
21.1			2.5	3.0
22.0				2.8
24.0				2.2
26.0				1.8
27.8				1.4

