

TADANO		30.5m + 13.0m					
5度		25度		45度		60度	
作業半径[m]	定格総荷重[t]	作業半径[m]	定格総荷重[t]	作業半径[m]	定格総荷重[t]	作業半径[m]	定格総荷重[t]
5.6	2.2	9.6	1.3	12.9	0.85	14.2	0.65
9.1	2.2	12.9	1.3	15.7	0.85	17	0.62
10.8	2.1	14.5	1.3	17.1	0.85	18.2	0.61
12.3	1.95	15.9	1.25	18.4	0.85	19.4	0.61
13.8	1.85	17.3	1.2	19.6	0.85	20.6	0.6
15.3	1.7	18.6	1.15	20.9	0.85	21.6	0.6
16.7	1.65	19.9	1.15	22.1	0.85	22.7	0.6
18.1	1.55	21.2	1.1	23.2	0.85	23.7	0.6
20.1	1.45	23	1.05	24.8	0.84	25.2	0.6
23.4	1.3	26.1	0.99	27.5	0.81	27.5	0.6
26.3	1.05	28.9	0.91	29.8	0.79		
27.4	0.95	29.8	0.85	30.7	0.79		
28.9	0.74	31.1	0.67	31.8	0.66		
30.4	0.57	32.4	0.52	32.8	0.52		
31.3	0.47	33.2	0.43	33.5	0.43		

KATO		30.5m + 13.0m					
5度		25度		45度		60度	
作業半径[m]	定格総荷重[t]	作業半径[m]	定格総荷重[t]	作業半径[m]	定格総荷重[t]	作業半径[m]	定格総荷重[t]
4.9	2.1	9.5	1.25	12.5	0.85	13.6	0.65
8.4	2.1	12.5	1.25	15.1	0.85	16.1	0.65
10.9	2.1	14.7	1.25	17.1	0.85	17.8	0.65
12.6	2.1	16.2	1.25	18.4	0.85	18.9	0.65
14.2	2.1	17.6	1.2	19.6	0.85	20.1	0.6
15.8	2	18.9	1.15	20.8	0.85	21.2	0.6
17.2	1.85	20.2	1.1	21.9	0.8	22.2	0.6
18.6	1.75	21.5	1.05	23	0.8	23.2	0.6
20	1.6	22.8	1	24.2	0.8	24.2	0.6
21.9	1.45	24.6	0.95	25.8	0.8	25.5	0.6
22.5	1.4	25.1	0.95	26.3	0.8	26	0.6
24.4	1.25	26.8	0.9	27.7	0.75		
26.2	1.15	28.4	0.9	29.1	0.75		
27.2	1.05	29.4	0.85	30	0.75		
28.7	0.85	30.7	0.75	31.1	0.75		
30.7	0.6	32.4	0.55	32.5	0.55		
31.1	0.55	32.8	0.5				
33.3	0.37						

